

## STILL EXU S22 Low lift pedestrian pallet truck

### Transport

EXU-S 22-



STILL Electric Low Lift Pallet Truck with Driver's Stand-on Platform EXU-S

- + 3,0 kW AC drive with 2 drive modes.
- + Platform suspension for shock absorption
- + Multi-functional operation console STILL Cockpit.
- + Access control via digicode system.
- + Electric steering with automatic return to the straight-ahead position
- + Speed reduction when cornering.
- + Central load-dependant suspended drive unit.
- + Many storage compartments (even for film rolls).

**Serial no.: F20177G00362**

**Year: 2016**

### Type

Basic model	EXU-S 22. 24 V Truck width b1= 720 mm. Robust twin castor wheels 2X140X54 mm.
Basic load-carrying capacity	2,200 KG
Basic capacity to lift height	130 MM

### Chassis

Platform	with access at the rear. Length l2 = 1225 mm with battery compartment Tray 70. Length l2 = 1310 mm with battery compartment Tray 71.
Battery compartment	Tray 70 for 24V. 300-465 Ah with roller track for battery change to side Battery can also be changed using a hoist
Fork dimensions	Length/width/overall width 1190 mm/ 172 mm/ 560 mm, Load distance x = 1023 mm

### Specification

Tyres load rollers	Polyurethane tandem 85 x 80 mm
Tyres - Drive wheel	polyurethane 250 x 100 mm
Supporting wheel	Polyurethane/Tandem 140 x 54 mm
Electric control	Optimised motor characteristics for energy saving operation at maximum speed
Work hour meter	Work Hour Meter
Combi-instrument	for wet battery. DBI and WHM combined with hoist cut-out.
Truck plug connection	SBE 160 red
Colour code	Safety orange/silver grey 2-colour. RAL 2000/RAL 9006
SC_500115_1_72	Latvian
Documentation	1 set of documentation comprising: 1 x operating and maintenance manual plus 1 x spare parts list.

**SIA Konekesko Latvija**

Tīraines iela 15

Rīga, Latvija, LV – 1058

Tālr: (+371) 67064300

Fakss: (+371) 67064301

**Battery**

Number of batteries per truck	1
Battery supplier	STILL
Battery maintenance type	low maintenance
Battery	24V 3PzS 465 STILL, 70
Tray	70
Battery plug connection	160A SBE red with handle
Water top-up system	STILL 24 V
Water top up kit	30 l with central filling, including shut off valve, flow indicator, connector and 4 m hose
Tray colour	RAL 9006 silver
Tray underside coating	Tray underside coated
Material price increment (MPI)	for battery 24 V / 3PzS 465 Ah, tray 70
Battery weight	405 kg

**Charger**

Battery charger	E 24/50 PXS
Charger	Pulse characteristics Traffic-light type charge level indication Data storage of the last 200 cycles (completion data) Standard USB connection Ambient temperature + 40 °C Mains supply E = 1x 230V , D= 3 x 400V, 50Hz Protection class (housing) IP 21
Charging time	Charging time 9 - 11 hours
Country-specific version	Version Latvia
Battery charger plug connector	160A SBE red
Mains connection	Mains connection E 230 V 50Hz
Mains plug	Earthed plug
Mains fuse protection	16 A
Weight	30.00 KG
Nominal connected load [kVA]	1.90 KW
Dimensions	500x300x260.mm

**Price: 5550 EUR w/o VAT**

**Gints Freidenfelds**[gints.freidenfelds@kesko.lv](mailto:gints.freidenfelds@kesko.lv)**Mob.:+37129165500**