

SIA Konekesko Latvija

Tīraines iela 15

Rīga, Latvija, LV – 1058

Tālr: (+371) 67064300

Fakss: (+371) 67064301

STILL Elektriskais krautņotājs FM-X17 ar diviem akumulātoriem un to maināmiem rāmjiem



STILL Electric Rider-Seated Reach Truck FM-X

- + High handling turnover rate and precise load handling also at high lift heights, thanks to ALS Active Load Stabilisation for mast heights over 3700 mm**
- + Maximum use of space due to high residual capacity up to 13 m lift height**
- + Optimum working conditions for the driver due to enhanced**

SIA Konekesko Latvija

Tīraines iela 15

Rīga, Latvija, LV – 1058

Tāl: (+371) 67064300

Fakss: (+371) 67064301

- ergonomic support with numerous adjustment options**
- + Intuitive control for focussed work with state-of-the-art operating devices such as Joystick or Fingertipp**
- + Outstanding visibility to all sides thanks to free-view mast and optimised overhead guard**
- + Easy-to-read display with detailed information e.g. operation status, speed, driving programmes, battery charge state etc.**
- + Powerful and maintenance free AC drive technology with energy recuperation for maximum energy efficiency**

Serial No. 511903G00441**Hours: 2271****Year: 2016****Type**

Basic model	STILL rider-seated reach truck FM-X 17, width = 1270 mm
Load capacity	1700 kg
Truck design	FM-X 14-17, standard version, rated load capacity 1400-1700 kg
Truck width	1,270 MM
Load wheel tyres	Diameter 285 mm, Polyurethane
Drive wheel tyre	Diameter 360 mm, Polyurethan
Battery tray	For 48 V / 480 - 620 Ah battery, tray 324 with roller track for battery change over the side, battery can also be changed by crane.
Truck version	Cold store version for up to -30° C, for in-out operation, lubricants, grease, hydraulic and gear box oil fit for cold store

Mast

Mast function fork carriage	Fixed mast Fork tilt with free-view side shift, side shift +/- 80 mm, designed for cold store operation; width of fork carriage: top 760 mm, bottom 650 mm incl. necessary hydraulics (4th function)
Mast	Triple .4200.
Closed height	4,200 MM
Free lift	3,330 MM
Rated lift	10,500 MM
Maximum height h4	11,370 MM
Capacity at max. lift	780 KG
Basic load-carrying capacity	1,700 KG
Basic capacity to lift height	6,800 MM
Maximum width	1,270 MM
ALS-active load stabilisation	Active load stabilisation for masts for closed height $h1 > = 3,700$ mm
Fork arms	1150 x 100 x 50 mm, 2A, LSP 600
Load backrest	height 800 mm

SIA Konekesko Latvija

Tīraines iela 15

Rīga, Latvija, LV – 1058

Tāl: (+371) 67064300

Fakss: (+371) 67064301

Tilt angle	3/3 degree forward/backward fork carriage tilt
Mast dissas.before dispatch	Mast disassembled for transport.

Cabin area

Overhead guard	overhead guard with head cushion
OHG depth/height	Dimensions standard overhead guard: height - 2200 mm, depth - 795 mm
Auxiliary equipment roof	Overhead guard support with mount for MMS or other auxiliary components.
Interior rear view mirror	Panoramic rear view mirror on drive end of the overhead guard for improved visibility when exiting aisles.
Driver seat	Hydraulically dampened comfort driver seat with imitation leather cover and heater. Stepless weight adjustment, tilt adjustment of back rest, horizontal adjustment and lumbar support.
Hydraulic controls	Joystick 4Plus single control for lifting, tilting and auxiliary hydraulic functions, incl. horn.
Drive control	Designed as foot and seat switch in combination with single pedal control and drive direction selection by rocker switch.
Steering system	Steering system fully electric 360°, height adjustment for steering wheel
Key switch	Key switch, lock 530

Specification

Hazard warning	Acoustic signal
Parameters hazard warning	Driving
Truck plug connection	160 A, DIN Rema
Colour code	Orange/silver-metal (lead/cadmium free)
Labelling	Latvian
Documentation	1 operation and maintenance manual and 1 spare parts list

Battery

Number of batteries per truck	2
Battery supplier	STILL
Tray	324
Battery maintenance type	low maintenance
Battery	48V 4PzS 620 STILL, 324
Battery plug	160A DIN Rema
<i>Material price increment (MPI)</i>	<i>for battery 48 V / 4PzS 620 Ah, tray 324</i>
Tray colour	RAL 2000 orange
Tray underside coating	Tray underside uncoated
Battery weight	939 kg

Charger

Charger	D 48/70 HFX
Charger	controlled characteristics energy saving by increased efficiency lower mains power because cos phi is approximately 1 Low charging current ripple leading to lower temperature increase in the battery Traffic-light type charge level indication (large, coloured indication, easy to read from a

SIA Konekesko Latvija

Tīraines iela 15

Rīga, Latvija, LV – 1058

Tālrunis: (+371) 67064300

Fakss: (+371) 67064301

Charging time	distance) Saving of the last charging data
Charger plug connector	Standard USB connection Ambient
Country-specific version	temperature + 40 ° C Protection class IP 21
Mains connection	Charging time 9 - 11 hours
Mains plug	160A DIN Rema
Mains fuse protection	Version Latvia
Weight	Mains connection D 400 V 50Hz
Nominal connected load [kVA]	CEE 16
Dimensions	16 A
	30.00 KG
	3.70 KW
	564x318x405 mm

Accessories

Batt. transport/change frame	2 pcs. for tray 324 with 2 roller tracks for transport and exchange, with battery safety device for quick battery change. Roller height adjustable
------------------------------	--

Price: 10500 EUR w/o VAT

Ar cieņu,

Gints Freidenfelds

Mob.: +37129165500

gints.freidenfelds@kesko.lv